Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 12

MSDS Number : 000000009901

Product Use Description : Refrigerant, Aerosol propellant, Carrier gas

Company : Honeywell International Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical (PROSAR): 1-800-498-5701 or +1-651-523-0309

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : slight

Hazard Summary : WARNING! Contains gas under pressure; may explode if

heated. This product is not flammable at ambient

temperatures and atmospheric pressure. Gas reduces oxygen

available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. Irritating to eyes and skin. Avoid contact with skin, eyes and clothing. At higher

Page 1 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

temperatures, (>250°C), decomposition products may include hydrochloric acid (HCI), hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling

Exposure Limit 2 ppm.

Potential Health Effects

Skin : Irritating to skin.

Rapid evaporation of the liquid may cause frostbite.

Eyes : Causes serious eye irritation.

May cause frostbite.

Ingestion : Unlikely route of exposure.

Effects due to ingestion may include:

Gastrointestinal discomfort

Inhalation : Gas reduces oxygen available for breathing.

Causes asphyxiation in high concentrations. The victim will

not realize that he/she is suffocating.

Inhalation may cause central nervous system effects. Vapours may cause drowsiness and dizziness.

Effects of breathing high concentrations of vapour may

include:

Cardiac arrhythmias

Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : CCl2F2

| Chemical Name | CAS-No. | Concentration |
|-------------------------|---------|---------------|
| Dichlorodifluoromethane | 75-71-8 | 100.00 % |

Page 2 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.

ASHRAE 34

Use water spray, alcohol-resistant foam, dry chemical or

Page 3 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

carbon dioxide.

Cool closed containers exposed to fire with water spray.

Specific hazards during

firefighting

: Contents under pressure.

Container may rupture on heating.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

In case of fire hazardous decomposition products may be

produced such as:

Gaseous hydrogen chloride (HCI).

Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

Special protective equipment

for firefighters

: Wear full protective clothing and self-contained breathing

apparatus.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is >= 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

The product evaporates readily.

Methods for cleaning up : Ventilate the area.

Page 4 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.

Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Keep away from heat.

Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

The product is not flammable.

Storage

Requirements for storage areas and containers

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Page 5 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Perform filling operations only at stations with exhaust

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

| Exposure Guidennes | | | | | | |
|--------------------------|---------|-------------------------------------|-------------|------|--|--|
| Components | CAS-No. | Value | Control | Upda | Basis | |
| | | | parameters | te | | |
| Dichlorodifluorom ethane | 75-71-8 | TWA: time weighted average | (1,000 ppm) | 2008 | ACGIH:US. ACGIH Threshold Limit Values | |

Honeywell

Genetron® 12

00000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

| Dichlorodifluorom ethane | 75-71-8 | REL: Recomm ended exposure limit (REL): | 4,950 mg/m3 (1,000 ppm) | 2005 | NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards |
|--------------------------|---------|--|----------------------------|------|--|
| | | | | | |

| Dichlorodifluorom | 75-71-8 | PEL: | 4,950 mg/m3 | 02 | OSHA_TRANS:US. |
|-------------------|---------|----------|-------------|------|------------------|
| ethane | | Permissi | (1,000 ppm) | 2006 | OSHA Table Z-1 |
| | | ble | | | Limits for Air |
| | | exposure | | | Contaminants (29 |
| | | limit | | | CFR 1910.1000) |
| | | | | | , |

| Dichlorodifluorom | 75-71-8 | TWA: | 4,950 mg/m3 | 1989 | Z1A:US. OSHA |
|-------------------|---------|----------|-------------|------|-----------------|
| ethane | | time | (1,000 ppm) | | Table Z-1-A (29 |
| | | weighted | | | CFR 1910.1000) |
| | | average | | | |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : slight

pH : Note: neutral

Melting point/freezing point : -158 °C

Boiling point/boiling range : -29.8 °C

Flash point : Note: not applicable

Evaporation rate : 380

Method: Compared to Butyl acetate.

Page 7 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Lower explosion limit : Note: None

Upper explosion limit : Note: None

Vapor pressure : 6,543 hPa

at 21.1 °C(70.0 °F)

13,486 hPa

at 54.4 °C(129.9 °F)

Vapor density : 4.2

Density : 1.33 g/cm3

Water solubility : 0.3 g/l

Solubility in other solvents : Medium: Methanol

Note: partly soluble

Medium: Diethylether Note: partly soluble

Partition coefficient: n-

octanol/water

: log Pow: 2.16

Note: The product is more soluble in octanol.

Molecular Weight : 120.91 g/mol

Global warming potential : 8,100

(GWP)

Ozone depletion potential

(ODP)

: 1

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Page 8 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Contains gas under pressure; may explode if heated.

Keep away from heat.

Keep away from direct sunlight. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to

avoid

: Finely divided aluminium

Potassium Calcium

Powdered metals

Aluminium Magnesium

Zinc

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as:

Gaseous hydrogen chloride (HCI). Gaseous hydrogen fluoride (HF).

Carbonyl halides Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 760000 ppm

Exposure time: 4 h

Species: rat

Sensitisation : Cardiac sensitization

Species: dogs

Note: Threshold - 50,000 ppm

Repeated dose toxicity : NOAEL (No observed adverse effect level): 10000 ppm

Note: Subchronic toxicity

Page 9 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Teratogenicity : Species: rat

Method: Not a teratogen

: Species: rabbit

Method: Not a teratogen

SECTION 12. ECOLOGICAL INFORMATION

Further information on ecology

Additional ecological

information

: Accumulation in aquatic organisms is unlikely.

This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.

Section 611 requires the following label text on all shipments

of this product:

Warning: Contains Dichlorodifluoromethane (HCFC-12), a substance which harms public health and environment by

destroying ozone in the upper atmosphere.

Refer to sections 610 and 612 for list of acceptable and

unacceptable uses for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1028

Proper shipping name : DICHLORODIFLUOROMETHANE

Page 10 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Class 2.2

Packing group

Hazard Labels 2.2

IATA UN/ID No. : UN 1028

Description of the goods : DICHLORODIFLUOROMETHANE

Class : 2.2 Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction : 200

(passenger aircraft)

IMDG UN/ID No. : UN 1028

Description of the goods : DICHLORODIFLUOROMETHANE

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL list.

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Existing Chemicals

Inventory (KECI)

: On the inventory, or in compliance with the inventory

Page 11 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act

: On the inventory, or in compliance with the inventory

China. Inventory of Existing

Chemical Substances

: On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 Components : The following components are subject to reporting levels

established by SARA Title III, Section 313: Dichlorodifluoromethane 75-71-8

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

CERCLA Reportable

Quantity

: 5000 lbs

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Dichlorodifluoromethane 75-71-8

: Dichlorodifluoromethane **New Jersey RTK** 75-71-8

Pennsylvania RTK : Dichlorodifluoromethane 75-71-8

Page 12 / 13

Honeywell

Genetron® 12

000000009901

Version 2.3 Revision Date 09/12/2012 Print Date 08/05/2014

WHMIS Classification : A: Compressed Gas

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

Global warming potential : 8,100

Ozone depletion potential : 1

(ODP)

SECTION 16. OTHER INFORMATION

| | HMIS III | NFPA |
|-----------------|----------|------|
| Health hazard | : 1 | 2 |
| Flammability | : 1 | 1 |
| Physical Hazard | : 0 | |
| Instability | : | 0 |

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 04/13/2009

Prepared by: Honeywell Performance Materials and Technologies Product Stewardship Group