Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® AZ-50 (R-507)

MSDS Number : 000000009882

Product Use Description : Refrigerant

Manufacturer or supplier's

details

Honeywell International Inc.

101 Columbia Road

Morristown, NJ 07962-1057

For more information call : 800-522-8001

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : very faint sweet

Classification of the substance or mixture

Classification of the : Gases under pressure, Liquefied gas

substance or mixture Simple Asphyxiant

GHS Label elements, including precautionary statements

Page 1 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Symbol(s) :



Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary statements : **Storage:**

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise

classified

: May cause frostbite.

May cause cardiac arrhythmia. May cause eye and skin irritation.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
Pentafluoroethane	354-33-6	50.00 %
1,1,1-Trifluoroethane	420-46-2	50.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If breathing is irregular or stopped,

administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do

Page 2 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

not give drugs from adrenaline-ephedrine group.

Skin contact : After contact with skin, wash immediately with plenty of water.

If there is evidence of frostbite, bathe (do not rub) with

lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a

physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.

Ingestion : Unlikely route of exposure. As this product is a gas, refer to the

inhalation section. Do not induce vomiting without medical

advice. Call a physician immediately.

Notes to physician

Treatment : Because of the possible disturbances of cardiac rhythm,

catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-

bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : The product is not flammable.

Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific hazards during

firefighting

: Contents under pressure.

This product is not flammable at ambient temperatures and

atmospheric pressure.

However, this material can ignite when mixed with air under

pressure and exposed to strong ignition sources.

Container may rupture on heating.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water

courses.

Vapours are heavier than air and can cause suffocation by

Page 3 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

reducing oxygen available for breathing.

Rapid evapouration of the liquid may cause frostbite. In case of fire hazardous decomposition products may be

produced such as: Hydrogen halides Hydrogen fluoride Carbon monoxide Carbon dioxide (CO2) Carbonyl halides

Special protective equipment

for firefighters

: In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit.

No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Immediately evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

Wear personal protective equipment. Unprotected persons

must be kept away.

Remove all sources of ignition.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

After release, disperses into the air.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing. Avoid accumulation of vapours in low areas.

Unprotected personnel should not return until air has been

tested and determined safe.

Ensure that the oxygen content is = 19.5%.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

The product evapourates readily.

Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE

Handling

Page 4 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Handling : Handle with care.

Avoid inhalation of vapour or mist.

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Use only in well-ventilated areas.

Pressurized container. Protect from sunlight and do not expose

to temperatures exceeding 50 °C.

Follow all standard safety precautions for handling and use of

compressed gas cylinders. Use authorized cylinders only.

Protect cylinders from physical damage.

Do not puncture or drop cylinders, expose them to open flame

or excessive heat.

Do not pierce or burn, even after use. Do not spray on a naked

flame or any incandescent material.

Do not remove screw cap until immediately ready for use.

Always replace cap after use.

Advice on protection against fire and explosion

The product is not flammable.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Storage

Requirements for storage areas and containers

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even

after use.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Storage rooms must be properly ventilated.

Ensure adequate ventilation, especially in confined areas.

Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Do not breathe vapour.

Avoid contact with skin, eyes and clothing.

Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : General room ventilation is adequate for storage and handling.

Perform filling operations only at stations with exhaust

Page 5 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

ventilation facilities.

Eye protection : Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Leather gloves

In case of contact through splashing:

Protective gloves Neoprene gloves

Polyvinyl alcohol or nitrile- butyl-rubber gloves

Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).

Wear cold insulating gloves/ face shield/ eye protection.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Wear a positive-pressure supplied-air respirator.

Vapours are heavier than air and can cause suffocation by

reducing oxygen available for breathing.

For rescue and maintenance work in storage tanks use self-

contained breathing apparatus.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Ensure adequate ventilation, especially in confined areas.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothing before re-use.

Keep working clothes separately.

Exposure Guidelines

Exposure Guidelines							
Components	CAS-No.	Value	Control parameters	Upda te	Basis		
Pentafluoroethan e	354-33-6	TWA : time weighted average	4,900 mg/m3 (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides		

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Pentafluoroethan e	354-33-6	TWA: time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1- Trifluoroethane	420-46-2	TWA : time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1- Trifluoroethane	420-46-2	TWA : time weighted average	3,400 mg/m3 (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas

Color : colourless

Odor : very faint sweet

pH : Note: neutral

Melting point/freezing point : Note: not determined

Boiling point/boiling range : -46.7 °C

Flash point : Note: not applicable

Evaporation rate : > 1

Method: Compared to CCI4.

Page 7 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Print Date 08/05/2014 Revision Date 06/02/2014

Lower explosion limit : Method: ASTM E-681

Note: None

Upper explosion limit : Method: ASTM E-681

Note: None

Vapor pressure : 10,611 hPa

> at 21.1 °C(70.0 °F) 25,289 hPa

at 54.4 °C(129.9 °F)

Vapor density : 3.43 Note: (Air = 1.0)

Density : 1.07 g/cm3 at 21.1 °C

Water solubility : 1.5 g/l

Partition coefficient: n-

: log Pow: 1.48

octanol/water

Test substance: Ethane, pentafluoro- (HFC-125)

Ignition temperature : > 750 °C

: > 250 °C Decomposition temperature

Note: To avoid thermal decomposition, do not overheat.

Global warming potential

(GWP)

Ozone depletion potential

(ODP)

: 3,850

: 0

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Page 8 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Print Date 08/05/2014 Revision Date 06/02/2014

Possibility of hazardous

reactions

: Hazardous polymerisation does not occur.

Conditions to avoid : Pressurized container. Protect from sunlight and do not

> expose to temperatures exceeding 50 °C. Decomposes under high temperature.

Some risk may be expected of corrosive and toxic

decomposition products.

Can form a combustible mixture with air at pressures above

atmospheric pressure.

Do not mix with oxygen or air above atmospheric pressure.

Incompatible materials to

avoid

: Potassium

Calcium

Powdered metals Finely divided aluminium

Magnesium

Zinc

Hazardous decomposition

products

: Halogenated compounds

Hydrogen fluoride Carbonyl halides Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

Pentafluoroethane : > 769000 ppm

Exposure time: 4 h

Species: rat

: LC50: > 540000 ppm 1,1,1-Trifluoroethane

Exposure time: 4 h

Species: rat

LC50: > 106 mg/l Exposure time: 4 h

Species: rat

Sensitisation

Pentafluoroethane : Cardiac sensitization

Page 9 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Species: dogs

Note: No-observed-effect level

75 000 ppm

Lowest observable effect level

100 000 ppm

1,1,1-Trifluoroethane : Cardiac sensitization

Species: dogs

Note: 1,1,1,2-tetrafluoroethane (HFC-134a): Cardiac

sensitisation threshold (dog): 80000 ppm.

Repeated dose toxicity

Pentafluoroethane : Species: rat

Application Route: Inhalation Exposure time: (4 Weeks) NOEL: 50000 ppm

Subchronic toxicity

1,1,1-Trifluoroethane : Species: rat

Application Route: Inhalation Exposure time: (90 d) NOEL: 40000 ppm Subchronic toxicity

Genotoxicity in vitro

Pentafluoroethane : Test Method: Ames test

Result: negative

1,1,1-Trifluoroethane : Test Method: Ames test

Result: negative

: Cell type: Human lymphocytes

Result: negative

: Cell type: Chinese Hamster Ovary Cells

Result: negative

Cell type: Human lymphocytes

Result: negative

Genotoxicity in vivo

1,1,1-Trifluoroethane : Species: mouse

Page 10 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Cell type: Bone marrow Application Route: Inhalation

Result: negative

Teratogenicity

Pentafluoroethane : Species: rabbit

Application Route: Inhalation exposure

NOAEL, Teratog: 50,000 ppm NOAEL, Maternal: 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Species: rat

Application Route: Inhalation exposure NOAEL,Teratog: 50,000 ppm

NOAEL, Maternal: 50,000 ppm

Note: Did not show teratogenic effects in animal experiments.

1,1,1-Trifluoroethane : Species: rat

Application Route: Inhalation exposure

NOAEL, Teratog: 40,000 ppm NOAEL, Maternal: 40,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Species: rabbit

Application Route: Inhalation exposure

NOAEL, Teratog: 40,000 ppm NOAEL, Maternal: 40,000 ppm

Note: Did not show teratogenic effects in animal experiments.

Further information : Acute toxicity Ethane, pentafluoro- (HFC-125): Cardiac

sensitisation threshold (dog): 75000 ppm. 1,1,1-

trifluoroethane (HFC-143a): Cardiac sensitisation threshold (dog): >250000 ppm. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evapouration of the liquid may cause frostbite. Irritating

to eyes and skin. Avoid skin contact with leaking liquid (danger of frostbite). May cause cardiac arrhythmia.

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability

Pentafluoroethane : Result: Not readily biodegradable.

Value: 5 %

Method: OECD 301 D

Further information on ecology

Additional ecological

information

: Accumulation in aquatic organisms is unlikely.
This product contains greenhouse gases which may

contribute to global warming. Do NOT vent to the atmosphere.

To comply with provisions of the U.S. Clean Air Act, any

residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

Note : This product is subject to U.S. Environmental Protection

Agency Clean Air Act Regulations Section 608 in 40 CFR Part

82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163

Proper shipping name : LIQUEFIED GAS, N.O.S.

(Pentafluoroethane, 1,1,1-Trifluoroethane)

Class 2.2

Packing group

Hazard Labels 2.2

IATA UN/ID No. : UN 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(Pentafluoroethane, 1,1,1-Trifluoroethane)

Page 12 / 15

Honeywell

Genetron® AZ-50 (R-507)

000000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Class : 2.2 Hazard Labels : 2.2 Packing instruction (cargo : 200

aircraft)

Packing instruction

: 200

(passenger aircraft)

IMDG UN/ID No. : UN 3163

Description of the goods : LIQUEFIED GAS, N.O.S.

(PENTAFLUOROETHANE, 1,1,1-

TRIFLUOROETHANE)

Class : 2.2
Hazard Labels : 2.2
EmS Number : F-C, S-V
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances : On TSCA Inventory

Control Act

Australia. Industrial : On the inventory, or in compliance with the inventory

Chemical (Notification and

Assessment) Act

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control : On the inventory, or in compliance with the inventory

Act

China. Inventory of Existing : On the inventory, or in compliance with the inventory

Page 13 / 15

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

Chemical Substances

NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

SARA 302 Components : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 Components : SARA 313: This material does not contain any chemical

> components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard

Sudden Release of Pressure Hazard

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

WHMIS Classification : A: Compressed Gas

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

Global warming potential : 3,850

Ozone depletion potential : 0

(ODP)

Honeywell

Genetron® AZ-50 (R-507)

00000009882

Version 2.6 Revision Date 06/02/2014 Print Date 08/05/2014

SECTION 16. OTHER INFORMATION

 HMIS III
 NFPA

 Health hazard
 : 1
 2

 Flammability
 : 1
 1

 Physical Hazard
 : 0
 0

 Instability
 : 0
 0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 03/28/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group