

# MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

**Material name** Stay-Silv® White Brazing Flux

0134

Version #

09-June-2011 Issue date 10-Sept-2014 **Revision date** Supersedes date 23-July-2014 CAS# Mixture

Metal brazing operations. Product use

**Manufacturer information** 

**MSDS Number** 

Manufacturer/Supplier Harris Products Group 4501 Quality Place Mason, Ohio 45040 US

custservmason@jwharris.com

513-754-2000 Telephone number

**Emergency Telephone** 

1-888-609-1762 (US, Canada, Mexico only)

**Numbers** 

Please quote 333988

#### 2. Hazards Identification

Physical state Solid.

White paste. **Appearance Emergency overview CAUTION** 

> May cause eye burns. Prolonged or repeated contact with the product may irritate the skin. Causes digestive tract burns. Dust is irritating to the eyes and respiratory tract. Harmful if inhaled, absorbed through skin, or swallowed. Possible adverse reproductive and developmental effects.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

**OSHA** regulatory status Potential health effects

Skin

Inhalation. Ingestion. Skin contact. Eye contact. Routes of exposure

May cause eye burns. Risk of serious damage to eyes. **Eyes** 

Prolonged or repeated contact with the product may irritate the skin. Harmful if absorbed through the skin. Hydrogen fluoride, a possible decomposition product, is extremely corrosive and a poison by all routes of entry. Hydrogen fluoride can penetrate the skin and produce burns, which may not be immediately painful or visible; the burns impact the lower layers of skin and bone tissue. Hydrogen fluoride exposures involving 20 percent of the body or more can be fatal through

systemic fluoride poisoning.

Harmful by inhalation. Dust irritating to respiratory tract. Prolonged inhalation may be harmful. Inhalation Harmful if swallowed. Ingestion may produce burns to the lips, oral cavity, upper airway, Ingestion

esophagus and possibly the digestive tract.

Skin. Bone. Kidneys. **Target organs** 

**Chronic effects** Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Sterility.

Prolonged overexposure to fluorides may increase fluoride content of bones and teeth, and may result in fluorosis, and brittleness of bones. Prolonged or repeated contact may dry skin and cause dermatitis. Edema. Kidney injury may occur. Refer to Section 11 Toxicological Information for

more details.

Contact with this material may cause burns to the eyes. Symptoms include itching, burning, Signs and symptoms

redness, and tearing of eyes. Prolonged or repeated contact with the product may cause irritation of skin. Itching, redness, burning of skin. Edema. Symptoms of overexposure may be headache,

dizziness, tiredness, nausea and vomiting.

The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic Potential environmental effects

organisms.

Stay-Silv® White Brazing Flux **CPH MSDS NA** 

# 3. Composition / Information on Ingredients

Components	CAS#	Percent
Potassium difluorodihydroxyborate	85392-66-1	> 50
Potassium fluoride	7789-23-3	20 - 30

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

#### 4. First Aid Measures

First aid procedures

Immediately rinse eyes with water. Remove any contact lenses, and continue flushing eyes with Eye contact

running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of

the eye and lids with water. Get immediate medical attention.

Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. A 2.5 Skin contact

pct calcium gluconate gel applied topically after skin has been thoroughly washed will help reduce

severity of symptoms. Get medical attention if irritation develops and persists.

Inhalation Remove person from contaminated area to fresh air. Apply artificial respiration if needed. Call a

physician if symptoms develop or persist.

Ingestion Do NOT induce vomiting. Immediately rinse mouth and drink a cupful of water. Never give anything

by mouth to an unconscious person. Get medical attention immediately.

**General advice** Show this safety data sheet to the doctor in attendance.

# 5. Fire Fighting Measures

Flammable properties

The product is not flammable.

Extinguishing media

Suitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials. Water spray, foam, dry powder

or carbon dioxide.

Protection of firefighters

Protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

#### 6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Avoid inhalation of dust from the spilled material. Wear

protective clothing as described in Section 8 of this MSDS. Do not touch damaged containers or

spilled material unless wearing appropriate protective clothing.

**Environmental precautions** 

**Methods for containment** 

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Should not be released into the environment. Prevent product from entering drains. Do not allow

material to contaminate ground water system.

Large Spills: Sweep up and place into a proper container for disposal. Avoid the generation of

dusts during clean-up.

Small Spills: Wipe up spilled material and place in a suitable container for disposal.

Never return spills in original containers for re-use. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. For waste disposal, see Section 13 of the MSDS.

Other information Clean up in accordance with all applicable regulations.

Stay-Silv® White Brazing Flux **CPH MSDS NA** 

Issue date: 09-June-2011

2/8

# 7. Handling and Storage

**Handling** Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

where dust is formed. Avoid inhalation of dust and fumes. Avoid contact with skin and eyes. Wear appropriate personal protective equipment (See Section 8). Do not get this material on clothing. Do not eat, drink or smoke when using the product. Wash thoroughly after handling. Avoid release to

the environment.

Storage Store in tightly closed original container in a dry, cool and well-ventilated place. Store in a closed

container away from incompatible materials. Do not store in container made of glass or silicate-based material. Keep away from food, drink and animal feedingstuffs. Keep out of the

reach of children.

# 8. Exposure Controls / Personal Protection

#### Occupational exposure limits

#### **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Fluorides (CAS 16984-48-8)	PEL	2.5 mg/m3
US. OSHA Table Z-2 (29 CFR 1910.1000)		

Components	Туре	Value	Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	Dust.

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	

### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value Form	
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3	

#### Canada, Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3

#### Mexico. Occupational Exposure Limit Values

Components	Туре	Value
Fluorides (CAS 16984-48-8)	TWA	2.5 mg/m3

#### **Biological limit values**

#### **ACGIH Biological Exposure Indices**

Components Value	Determinant	Specimen	Sampling Time
Fluorides (CAS 16984-48-8)3 mg/l	Fluoride	Urine	*
2 mg/l	Fluoride	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Stay-Silv® White Brazing Flux CPH MSDS NA

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of **Engineering controls** 

inhalation of dust. Shower, hand and eye washing facilities near the workplace are recommended.

Personal protective equipment

Wear safety glasses with side shields (or goggles). Eye / face protection

Chemical resistant clothing is recommended. Skin protection

Respiratory protection Use a respirator when local exhaust or ventilation is not adequate to keep exposures below the

> TLV. In a confined space a supplied respirator may be required. Selection and use of respiratory protective equipment should be in accordance with OSHA General Industry Standard 29 CFR

1910.134; or in Canada with CSA Standard Z94.4.

Wear protective gloves (i.e. latex, nitrile, neoprene). Hand protection

Always observe good personal hygiene measures, such as washing after handling the material **General hygiene** and before eating, drinking, and/or smoking. Routinely wash work clothing and protective considerations

equipment to remove contaminants.

# 9. Physical & Chemical Properties

**Appearance** White paste.

Solid. Physical state **Form** Paste. Color White. Odor Odorless. Odor threshold Not available. Not available. рH Not available. Vapor pressure Not available. Vapor density Not available. **Boiling** point Not available. Melting point/Freezing point Solubility (water) Moderate. 1.5 - 1.7 Specific gravity Flash point Not available.

Flammability limits in air, upper, % by volume

Not available.

Flammability limits in air,

lower, % by volume

Not available.

**Auto-ignition temperature** Not available.

#### 10. Chemical Stability & Reactivity Information

Chemical stability Material is stable under normal conditions. Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Strong acids. Halogenated compounds. Silicate-based materials. Incompatible materials

**Hazardous decomposition** 

products

Hydrogen fluoride, fluorine-, boron- and potassium-containing compounds.

Stay-Silv® White Brazing Flux **CPH MSDS NA** 

Issue date: 09-June-2011

# 11. Toxicological Information

Toxicological data

Components Species **Test Results** 

Potassium difluorodihydroxyborate (CAS 85392-66-1)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat 744 mg/kg

Potassium fluoride (CAS 7789-23-3)

Acute Oral

LD50 Rat 245 mg/kg

Sensitization Not classified.

May cause eye burns. Prolonged or repeated contact with the product may irritate skin. **Acute effects** 

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Harmful if inhaled, absorbed through skin, or swallowed.

Local effects May cause eye burns. Causes respiratory tract irritation. Prolonged or repeated contact with the

product may irritate skin.

Chronic effects Prolonged exposure may cause chronic effects. May cause damage to the kidneys. Repeated

exposure to fluorides may cause excessive calcification of the bone and calcification of ligaments of the ribs, pelvis and spinal column. Exposure to extremely high levels of fluorides can cause abdominal pain, diarrhea, muscular weakness, and convulsions. In extreme cases it can cause

loss of consciousness and death.

Subchronic effects Kidney injury may occur.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

**ACGIH Carcinogens** 

Potassium difluorodihydroxyborate (CAS 85392-66-1) A4 Not classifiable as a human carcinogen. Potassium fluoride (CAS 7789-23-3) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Potassium fluoride (CAS 7789-23-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

No epidemiological data is available for this product. **Epidemiology** 

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Reproductive effects Possible reproductive hazard.

**Teratogenicity** May cause birth defects. Avoid exposure to women during early pregnancy.

Symptoms and target organs Contact with this material may cause burns to the skin, eyes and mucous membranes. Symptoms

include itching, burning, redness, and tearing of eyes. Itching, redness, burning of skin.

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Target

organs: Skin. Bones. Kidney.

**Further information** Symptoms may be delayed.

12. Ecological Information

**Ecotoxicological data** 

Components **Species Test Results** 

Potassium difluorodihydroxyborate

Aquatic

Fish LC50 Brachydinio rerio 750 mg/l, 96 hours

Stay-Silv® White Brazing Flux **CPH MSDS NA**  **Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment. Large amounts of the product may affect the acidity (pH-factor) in water with possible risk of

harmful effects to aquatic organisms.

**Environmental effects**An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Aquatic toxicity Not classified.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulation / accumulation

Not available.

Mobility in environmental

media

The product is partly soluble in water. May spread in the aquatic environment.

# 13. Disposal Considerations

Waste codes

**Disposal instructions**Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all

applicable regulations.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

DOT Product not regulated as Dangerous Good.

IATA Product not regulated as Dangerous Good.

IMDG Product not regulated as Dangerous Good.

TDG Product not regulated as Dangerous Good.

# 15. Regulatory Information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Not controlled

Drug Enforcement

Administration (DEA) (21 CFR

1308.11-15)

Stay-Silv® White Brazing Flux CPH MSDS NA

902265 Version #: 03 Revision date: 10-Sept-2014 Issue date: 09-June-2011

Yes

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS Canadian regulations

contains all the information required by the CPR.

WHMIS status Controlled WHMIS classification D2B - TOXIC

# WHMIS labeling

#### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

State regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Potassium fluoride (CAS 7789-23-3)

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance Not listed.

**US. Massachusetts RTK - Substance List** 

Not regulated.

United States & Puerto Rico

US. New Jersey Worker and Community Right-to-Know Act

Potassium fluoride (CAS 7789-23-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Potassium fluoride (CAS 7789-23-3)

**Mexico regulations** This safety data sheet was prepared in accordance with the Official Mexican Standard

(NOM-018-STPS-2000).

Stay-Silv® White Brazing Flux CPH MSDS NA

902265 Version #: 03 

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 3\* Flammability: 0

Physical hazard: 0

**NFPA** ratings



**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available.

Prepared by Not available.